





All-in-One Strikes by BEST

These versatile All-in-One Strikes are designed for offset and centerline latch entry.

With 1500 pounds of holding force, BEST All-in-One Strikes combine strength and convenience in a versatile, easy to install design. With the sawtooth adjustment locator, installers can adjust the strike to align with a wide variety of mortise locks with offset latches eliminating the need to order special faceplates making BEST All-in-One Strikes versatile and easy to install.

- Energy: 375mA¹ Field-selectable 12/24VDC,12-24VAC²
- Fire-Rated: Optional 3-hour Model Available³
- **Strength:** 1500lbf Static 70ft-lb Dynamic
- · Latch Monitor: Plug-in Accessory Available
- Endurance: 500,000 Cycles
- Warranty: Five-year (Limited)
- · Mode: Fail-Secure and Fail-Safe

Versatile, convenient and easy to install.

These electric strikes—featuring an adjustable deadbolt keeper and deadlatch ramp—combine strength and convenience in an attractive, sleek and easy-to-install design.

Product Specifications							
1-1/4" (32mm) W x 4-7/8"H (124mm)							
1-3/4"D (45mm)							
Mortise, cylindrical and mortise exit device							
Hollow metal, aluminum and wood							
1/2" (12.7mm) to 3/4" (19mm)							
Plug-in wire							
Non-handed							
BES-F2LM Latch monitor plug-in kit (2A @ 24VDC)							
32D Brushed Stainless Steel							
Five-year limited							
UL 294 Listed for Access Control Unit Accessory (6th Edition) UL 1034 burglary-resistant Listed UL 10C, 3-hour fire-rating Listed³ CAN/ULC S104, 3-hour fire-rating Listed³ Certified to ANSI/BHMA standard A156.31, Grade 1, endurance 500,000 cycles							

Model	Mode	Volts	Duty	Sound	Amps AC	Ohms*
BES-F2164	Fail Secure	12VAC/VDC	Continuous	Silent	0.375	37
		24VAC/VDC			0.190	148
		12-24VDC	Intermittent	Buzz	0.280-0.565	37
BES-2364	Fail Safe	12VDC	Continuous	Silent	0.375	37
		24VDC			0.190	148

Intermittent Duty: Energized less than one minute with duty ratio 1:5 Continuous Duty: Energized one minute or more

^{*}Nominal resistance at +25°C ± 7% tolerance







Deadbolt Plug

Features

BEST All-in-One Strikes

- Modular design: compatible with most locks; no special faceplates required; non-handed
- **Adjustable:** deadbolt keeper and deadlatch ramp—up to 5/16" of strike for precise alignment with lockset; keeper shims for horizontal adjustment‡—1/16" (1.5mm) and 1/8" (3mm)—for up to 1/8" (3mm)
- Run cool operation: solenoid design prevents keeper from heating up
- Heavy-duty construction: stainless steel with brushed stainless steel finish (32D)
- Holding force: up to 1500lbf (680kgf)
- Easy installation: non-handed; fits HES 1006 (1003) frame cutout (hollow metal)
- **Secure:** accommodates up to 3/4" latch projection; up to 1" deadbolt (night-latch function only, bolt will not release)
- Included: faceplate, trim plate and anti-tamper security screws for centerline latch entry; star and security driver bit; and, adhesive paper template
- Field selectable voltage input: accommodates 12 or 24VDC and 12 to 24VAC
- Low current draw: 0.19 Amps @24VDC; plug-in wire connector
- Patents: US patent 9,580,935 and Canadian patent 2,850,072
- · Warranty: five-year limited

Frame Type



Hollow Metal



Aluminum



Wood

Door Lock Type



Mortise



Cylindrical



Exit Device







¹ Max at 12VDC

² 12-24VAC not available with 2364 model

³ Fire-rated (F) model only. 3-hour for single swing, 90 minutes for standard pair of doors.

BA-0336 05/21

For questions about ordering and to be sure you get the right configuration for your needs, contact your BEST dormakaba sales representative. 6161 East 75th Street, Indianapolis, IN 46250 USA | 855-365-2407 | bestaccess.com

