



How to order SL6000 series

Series	Spring Size	Options	Arm	Cover Options	Fastners	Finish
SL60	14	DA	ARP	SPC	SNDTPK	689

(Bold Standard)

Spring size

14	Adjustable size 1-4 to meet barrier-free ADA requirements
36	Adjustable size 3-6

Finishes (Painted)		Options	
600	Primed	DA	Delayed Action
689	Aluminum (Standard)		
690	Statuary bronze		
691	Dull bronze		
693	Black		
695	Dark duranodic bronze		
696	Gold		
		Cover options	
		SPC	Slim Plastic

Custom Color (RAL color)
Designer color match


ARM descriptions

ARP	Round form arm, tri-pack (standard)	ISJH	Heavy duty top jamb arm with hold open and stop for 3-1/2–6-1/2" reveal
ARJ	Top jamb-round form arm for 4–8" reveal	SISJ	Heavy duty top jamb arm with compression stop for 3-1/2–6-1/2" reveal
A08P	Secured round form arm, tri-pack	SISJH	Heavy duty top jamb arm with hold open and compression stop for 3-1/2–6-1/2" reveal
FH	Friction hold open arm	SPA	Heavy duty parallel arm
FHP	Friction hold open arm, tri-pack	SPAT	Heavy duty parallel arm with thumb-turn hold open
FHJ	Top jamb friction hold open arm for 4–8" reveal	T	Track arm, pull side door mounted
PH	Regular/Top jamb plunger hold open arm	JT	Jamb track, pull side frame mounted
DS	Heavy duty parallel arm with stop	PT	Push track arm, push side soffit mounted
DST	Heavy duty parallel arm with hold open and stop	TDE	Track arm double egress, pull side frame mounted
SDS	Heavy duty parallel arm with compression stop	FT	Flush track arm, push side transom mounted
SDST	Heavy duty parallel arm with hold open and compression stop	TH	Track arm with hold open, pull side door mounted
IS	Heavy duty regular/top jamb arm with stop	JTH	Jamb track with hold open, pull side frame mounted
ISH	Heavy duty regular/top jamb arm with hold open and stop	PTH	Push track arm with hold open, push side soffit mounted
SIS	Heavy duty regular/top jamb arm with compression stop	TDEH	Track arm with hold open double egress, pull side frame mounted
SISH	Heavy duty regular/top jamb arm with hold open and compression stop	FTH	Flush track arm with hold open, push side transom mounted
ISJ	Heavy duty top jamb arm with stop for 3-1/2–6-1/2" reveal	LA	Less arm

Fasteners

SNTPK70	Standard self-drilling, self tapping and through bolts for steel or aluminum door and frame applications (replacement pack)
TX70	Torx security screws

Certifications

 ANSI / BHMA 156.4 Grade 1



ANSI/ICC A117.1 and ADA for barrier-free accessibility (size 1-4, when adjusted to size 1)



UL10C listing; UL 228 & CAN / ULC-S133

For questions about ordering and to be sure you get the right configuration for your needs, [contact your BEST dormakaba sales representative](#).
6161 East 75th Street, Indianapolis, IN 46250 USA | [855-365-2407](tel:855-365-2407) | bestaccess.com