



# Cabinet & Wardrobe Hardware by BEST



Trusted experts. Proven reliability. Simply BEST.

### **TABLE OF CONTENTS**

Wardrobe	pivots
Cabinet hin	

2-4

Notes .

#### Wardrobe Pivots

340 – [ANSI A8753] – Standary duty – steel – plated or prime coated finishes

- For flush, recessed or overlay doors 1-1/8" (28.6 mm) to 1-3/8" (35 mm) thick not exceeding 75 lbs. (34 Kg)
- · Only pivot of its type suitable for floor-to-ceiling doors
- · Clean appearance, only hinge pivot shows when door is closed
- Door can be opened 180°
- Elongated screw holes make alignment simple
- · Separable leaves of the top assembly permit fast installation
- · Bushing at the pivot point assure smooth, silent operation.







Right hand illustated

.6-7

	Gauge					Case W	eight
Catalog Number	Inches	(mm)	Flat Head Wood Screws/Per Set	Sets Per Box*	Sets Per Case	Lbs.	(Kg)
340	.131	[3.3]	8 -12 x 3/4	1	20	17	[8]

15/16

\*Set consists of one top hinge and one bottom hinge Handed. Specify right hand or left hand

**BEST** Cabinet & Wardrobe Hardware

2

#### Wardrobe Pivots

341 – (ANSI A8773) – Standary duty – steel – plated or prime coated finishes

- For flush, or recessed doors 1-1/8" (28.6 mm) to 1-3/8" (35 mm) thick not exceeding 75 lbs. (34 Kg)
- Top header and bottom side frame mounted
- Suitable for floor-to-celing doors
- Door can be opened 180°
- Elongated screw holes for easy alignment
- Separable leaves of the bottom assembly for quick, easy installation
- Bushing at the pivot point assure smooth, silent operation
- · Edge mortise door leaves standard practice





Right hand illustated





	Gauge					Case W	eight
Catalog Number	Inches	(mm)	Flat Head Wood Screws/Per Set	Sets Per Box*	Sets Per Case	Lbs.	(Kg)
341	.131	(3.3)	7 -12x 1 2 -12 x 11/4	1	20	14	[6.3]

\*Set consists of one top hinge and one bottom hinge Handed. Specify right hand or left hand



### Wardrobe Pivots

327 – (ANSI A8782) – Heavy weight – steel – satin chrome (26D) plated

- For overlay doors 1-3/8" (35 mm) to 1-3/4" (44 mm) thick doors not exceeding 150 lbs. (60 Kg)
- Ideal for wardrobe doors
- Bearings take vertical and lateral loads
- Designed for mullion or face frame mounting
- Doors can be installed floor-to-ceiling
- · Screw holes allow for vertical and horizontal adjustment
- Doors can be opened 180°
- Non-Handed







Right hand illustated

Catalog	26D	6D Gauge					Carton	Weight
	EDP Number	Inches	(mm)	Flat Head Wood Screws/Per Set	Sets Per Box*	Sets Per Case	Lbs.	(Kg)
327	35-0043	.200	(5)	10 -12 x 1-1/4	]	20	34	(15.4)

\*Set consists of one top hinge and one bottom hinge

Handed. Specify right hand or left hand

342 – (ANSI A8783) – Standary duty – steel – plated or prime coated finishes

· For overlay doors 1-1/8" (28.6 mm) to 1-3/8" (35 mm) thick doors not exceeding 75 lbs. (34 Kg)

- Designed for mullion or face frame mounting
- Suitable for floor-to-ceiling doors
- Doors can be opened 180°
- Elongated screw holes for easy alignment
- Mortised door leaves Standard practice
- Bushings at the pivot point assure smooth, silent operation
- Non-Handed





2 1/16"



	Gauge					Case Weight	
Catalog Number	Inches	(mm)	Flat Head Wood Screws/Per Set	Sets Per Box*	Sets Per Case	Lbs.	(Kg)
342	.131	[3.3]	10 -12 x 1	1	20	18	(8)

\*Set consists of one top hinge and one bottom hinge Handed. Specify right hand or left hand



## **Cabinet Hinges**

1592 – Button tip – steel – satin chrome (26D) finish

- HT1592 Hospital tip steel satin chrome (26D) finish
- Made of heavy .088" gauge steel
- For 3/4" (19 mm) thick overlay doors
- Has interleaf design for close door fit
- Elongated screw holes for easy vertical and horizontal alignment







Catalog	Size Le Frame	ngth of Leaf					Cartor	n Weight
Number	Inches	(mm)	Flat Head Wood Screws/Per Set	Pieces Per Pack	Packs Per Box	Packs Per Case	Lbs.	(Kg)
1592 & HT1592	2-3/4"	(70)	16 -8 x 5/8	2	5	50	40	(18)



Notes:	

Notes:	





**CORPORATE HEADQUARTERS** 6161 EAST 75TH STREET INDIANAPOLIS, IN 46250 USA

Phone 855-365-2407

bestaccess.com

For questions about ordering and to be sure you get the right configuration for your needs, contact your BEST dormakaba sales representative. 6161 East 75th Street, Indianapolis, IN 46250 USA | 855-365-2407 | bestaccess.com

BEST is a trademark of dormakaba Holding<sup>®</sup> 2021 All rights reserved. BEST is a member of the dormakaba Group, one of the top three providers for access and security solutions, globally.

dormakaba